



Available Accessories



Extender 1.4x &
Extender 2x



ADS / $\frac{1}{8}$ Technology
Angenieux Data System for lens data transfer
 $\frac{1}{8}$ trademark is property of Cooke Optics Ltd



DSLR Mounts



Wide Angle 0.75X

Servo Unit
Available Soon

Optimo 15 - 40

Lightweight Series

- » Extremely fast aperture of T2.6 with no ramping
- » 320° focus rotation with over 50 precise focus witness marks and no breathing
- » Superior optical performance rivaling prime lenses at equivalent focal lengths
- » Available with PL mount. PV, Nikon and Canon mounts available upon request
- » Calibrated focus marks available in feet or meters

Zoom Ratio: 2.7X
Focal Length: 15 - 40 mm
Aperture: f/2.4 – T2.6
MOD: 2 ft – 0.6 m
Internal Focus: Yes
Image Coverage: S35+: 31.4 mm diagonal

Weight (approx.): 4.2 lbs – 1.92 kg
Length: 186 mm
Front Diameter: 114 mm

Field of view for 35 mm Academic (22x16 mm)

Focal Length:	15 mm	40 mm
Horizontal angular field of view:	73°	31.2°
Object dimensions at MOD (mm):	611x437	230x169